


DETAIL A:



1	2	3	4	5	6	7	8	9	10	11	12	13	14	15
VSS/K	VDD	VO	RS	R/W	E	DB0	DB1	DB2	DB3	DB4	DB5	DB6	DB7	A

NOTES:

- 1.DISPLAY TYPE: STN/Y-G MODE
- 2.VIEWING DIRECTION: 6:00
- 3.POLARIZER MODE: TRANSFLECTIVE/POSITIVE
- 4.DRIVE METHOD: 1/16 DUTY 1/5 BIAS
- 5.LCD OPERATING VOLTAGE: 4.5V
- 6.OPERATING TEMP: -20°C~+70°C
- 7.STORAGE TEMP: -30°C~+80°C
- 8.CONTROLLER: S6A0069X01-COCX(KS0066UP-00CC)
- 9.BACKLIGHT: LED
- 10.BEZEL IS TO BE PAINTED BLACK
- 11.ALL UNMARKED TOLERANCE: ±0.3



MULTI-INNO TECHNOLOGY CO.,LTD.

DRAWN BY:	TITLE: MI1202A	
CHECKED BY:	DWG NO: G-4	
APPROVED BY:	DWG NAME:	UNIT: mm
CONFIRMED BY:	SHEET NO: OF	