

连接器3

1	Eye1-1
2	Eye1-2
3	干簧管开关
4	Reset
5	电池负极
6	电池正极

连接器2

功能	1	2	3
4	DOWN	UP	MODE
5	ENTER	CANCEL	

连接器1

1	扬声器输出1
2	扬声器输出2


REV.	DESCRIPTION	BY	DATE
-	RELEASED	P.L	06/28/05
A	ECO#020712	P.L	07/23/05
B	ECO#020803	P.L	08/05/05

技术要求:

- LCD 类型: HTN
- LCD偏光片: TRANSLFECTIVE/POSITIVE.
- 视角方向: 12: 00.
- 驱动模式: 1/32 DUTY; 1/6 BIAS.
- 工作电压:  $V_{op}=5.8V$ .
- 工作温度:  $0^{\circ}C$  TO  $+50^{\circ}C$ .
- 存储温度:  $-10^{\circ}C$  TO  $+60^{\circ}C$ .
- 黄绿色 (Y-G) 背光灯的输入电流: 60 mA; 输入电压: 4.1V.

10		连接器1	1		2 PIN WAFER
9		连接器2	1		5 PIN WAFER
8		连接器3	1		6 PIN WAFER
7		锂电池	1	CR2032	
6	2501CLIP01	电池夹	1		
5	2501ASM-33	电路板	1		2501PCB01 装配电路板
4		不锈钢自攻螺钉	2	ST2. 2X4. 5	GB/T845-1985
3	2501HSC02	热压斑马纸	1		
2	2501LCD01	液晶显示器	1		
1	2501LED01	LED背光灯	1		
序号	图号	名称	数量	规格	备注

TOLERANCE		REV: B
>0~6 ±0.10	>120~300 ±0.50	SHEET: 1 OF 1
>6~30 ±0.20	>300~500 ±0.80	SCALE: N.T.S.
>30~120 ±0.30	>500 ±1.20	UNITS: MM
// ⊥ ◎ ±0.10;	ANGLE: ±3.0°	APPROVALS
		DWN Lina DATE Aug-05
		CHK
		APP

 **广州市龙宇电子有限公司**  
Kingtronics Display Technologies Ltd., Co.

**DRAWING NO: 2501MOD**

**MODEL NUMBER: KC2501**

**DATE: 05-Aug-2005**

DO NOT SCALE THIS DRAWING. PROJECTION