


PIN	SYMBOL	PIN	SYMBOL
1	NC	20	VOUT
2	PS0	21	C5+
3	PS1	22	C3+
4	CSB	23	C1-
5	RESETB	24	C1+
6	RS	25	C2+
7	RW_WR	26	C2-
8	E_RD	27	C4+
9	DB0	28	REF
10	DB1	29	VEXT
11	DB2	30	INTRS
12	DB3	31	V4
13	DB4	32	V3
14	DB5	33	V2
15	DB6	34	V1
16	DB7	35	V0
17	VDD	36	VR
18	VCI	37	OSC1
19	VSS	38	NC

- NOTES:
- DISPLAY TYPE: FSTN
 - VIEWING DIRECTION: 6:00
 - POLARIZER MODE: TRANSLLECTIVE/POSITIVE
 - OPERATING TEMP: -20°C~+70°C
 - STORAGE TEMP: -30°C~+80°C
 - LCD OPERATING VOLTAGE: 12.3V
 - LOGIC VOLTAGE(VDD): 3.0V
 - DRIVE METHOD: 1/128 DUTY 1/12 BIAS
 - CONTROLLER: S6B0741X01-30XN
 - BACKLIGHT: EL;GREEN
 - UNMARKED TOLERANCES: ±0.3mm
 - THE CONTROLLED DIMENSION MASK TO BE
 - ROHS COMPLIANT



MULTI-INNO TECHNOLOGY CO.,LTD.

G-5	ADD GLUE ON REAR SIDE OF EL
G-4	ADD REMOVE TAPE
G-3	ADD ADHESIVE TAPE AT REAR SIDE
G-2	CHANGE LCD, V/A AND A/A

DRAWN BY:	TITLE: MI128128G-T	
CHECKED BY:	DWG NO:	
APPROVED BY:	DWG NAME:	SHEET NO: 1 OF 1
CONFIRMED BY:		