



PIN ASSIGNMENT	PIN NO	SYMBOL
1	VCOM	
2	DVD0	
3	DVD0	
4	NC	
5	RESET	
6	STRVB	
7	GND	
8	PIND0	
9	PIND0	
10	GND	
11	PIND1	
12	PIND1	
13	GND	
14	PIND2	
15	PIND2	
16	GND	
17	PIND3	
18	PIND3	
19	GND	
20	PIND3	
21	PIND3	
22	GND	
23	NC	
24	NC	
25	GND	
26	NC	
27	NC	
28	SELB	
29	AVDD	
30	GND	
31	LED_K	
32	LED_K	
33	SHLR	
34	UPDN	
35	VGL	
36	NC	
37	NC	
38	VGH	
39	LED_A	
40	LED_A	

- NOTES:
1. DISPLAY TYPE: TFT/TRANSMISSIVE/NORMALLY BLACK.
 2. VIEWING DIRECTION: FULL VIEWING ANGLE.
 3. OPERATING VOLTAGE: DVDD=3.3V.
 4. DRIVER IC: LU5120+LU6150C.
 5. OPERATING TEMP.: -20°C ~ 70°C.
 6. STORAGE TEMP.: -30°C ~ 80°C.
 7. BACKLIGHT: Z7-CHIP WHITE LED, IF=180mA, VF=8.7V~9.9V.
 8. SURFACE LUMINANCE: 650cd/m²(TYP.)
 9. TOP POLARIZER SURFACE TREATMENT: TBD.
 10. GENERAL TOLERANCE: ±0.2mm.
 11. ROHS COMPLIANT.

<https://www.displayfuture.com>

VER.	DESCRIPTION	REVISER	DATE
01	FIRST ISSUE	RITA	2017.12.05
01	REVISED DESCRIPTION		



DRAWN BY:	2017.12.05	SCALE : 1/1	MODULE P/N:
CHECKED BY:		UNIT: mm	DF-TFN0695FB-M4
APPROVED BY:			DESCRIPTION:
VERSION NO.:	01		TFT MODULE