


NOTES:


1. 3.5" PROJECTIVE CAPACITIVE TOUCH PANEL.
2. OPERATING VOLTAGE: VDD=VDDIO=3.3V.
3. COVER GLASS + SENSOR GLASS + FPCA.
4. RESOLUTION: 320 X 240 DOTS.
5. CONTROLLER: FT5446DQS (SMT); I2C INTERFACE.
6. MULTI-FINGER: UP TO 5.
7. HARDNESS OF COVER SURFACE: 7H.
8. TRANSMITTANCE: >=85%.
9. ELECTRODES: 13 X 10.
10. UV GLUE AROUND CHIP PINS.
11. GROUNDING LAYERS ON BOTH SIDES OF FPC.
12. ITO PATTERN ON BOTH SIDES CAN NOT BE VISIBLE AT HIGH BRIGHTNESS.
13. 0.5MM THICKNESS OF TINY COMPRESSIBLE GASKET.
14. PROTECTIVE CIRCUITS AT INPUT SIGNALS LINES.
15. PROTECTIVE FILMS ON FRONT AND BACK SIDES OF MODULE.
16. GENERAL TOLERANCE: ±0.2.
17. OPERATING TEMP.: -20C-70C;
STORAGE TEMP.: -30C-80C.
18. RoHS COMPLIANT.

CTP FPC:


1	VSS
2	VDD
3	SCL
4	NC
5	SDA
6	NC
7	/RST
8	NC
9	/INT
10	VSS



01	FIRST ISSUE	2016.09.05
VER.	REVISED DESCRIPTION	DATE



Display Future Ltd

DRAWN BY:		SCALE : 1/1	MODULE P/N:
CHECKED BY:		UNIT:	DF-SSC0354---M1
APPROVED BY:			DESCRIPTION:
VERSION NO:	01		CTP MODULE