


CTP FPC:

1	VSS
2	VDD
3	SCL(SSCL)
4	NC(SCK)
5	SDA(MOSI)
6	NC(MISO)
7	RST
8	WAKE
9	INT
10	VSS

- NOTES:
- 3.5 INCH PROJECTIVE CAPACITIVE TOUCH PANEL.
AR COATING ON SURFACE OF COVER;
 - OPERATING VOLTAGE: VDD=3.3V.
 - COVER GLASS + SENSOR GLASS + FPCA.
 - RESOLUTION: 320 X 480 DOTS.
 - IC DRIVER: FT5206 (SMT).
 - MULTI FINGER: UP TO 5.
 - HARDNESS OF COVER SURFACE: 7H.
 - TRANSTTANCE: >=85%.
 - ELECTRODES: 14 X 10.
 - UV GLUE AROUND CHIP PINS.
 - GROUNDING LAYERS ON BOTH SIDES OF FPC.
 - ITO PATTERN ON BOTH SIDES CAN NOT BE VISIBLE AT HIGH BRIGHTNESS.
 - 0.5MM THICKNESS OF TINY COMPRESIBLE GASKET.
 - PROTECTIVE CIRCUITS AT INPUT SIGNALS LINES.
 - PROTECTIVE FILMS ON FRONT AND BACK SIDES OF MODULE.
 - OPERATING TEMP.: -20C TO 70C;
STORAGE TEMP.: -30 TO 80C;
 - RoHS COMPLIANT.
 - GENERAL TOLERANCE: ±0.2MM.

<http://www.displayfuture.com>



DRAWN BY:		SCALE : 1/1	MODULE P/N:
CHECKED BY:		UNIT: mm	DF-SSC0356---M1
APPROVED BY:			DESCRIPTION:
VERSION NO:	02		CTP MODULE

02	Modify electrodes from 15*10 to 14*10	20151207
01	First issue	20150513
VER.	REVISED DESCRIPTION	DATE